



6913LLU Bearing 2D drawings and 3D CAD models

65 mm x 90 mm x 13 mm NTN 6913LLU deep groove ball bearings

Bearing No. 6913LLU

Size	65x90x13 mm
Bore Diameter	65 mm
Outer Diameter	90 mm
Width	13 mm
d	65 mm
D	90 mm
B	13 mm
C	13 mm
r min.	1 mm
da min.	70 mm
da max	71,5 mm
Da max.	85 mm
ra max.	1 mm
Weight	0,206 Kg
Basic dynamic load rating (C)	17,4 kN
Basic static load rating (C0)	16,1 kN
Reference speed	4 000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.207
EAN	4547359587845
Product Group	B00308
Enclosure	2 Seals



Shandong Jiangshan Industrial Develop...

Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	65MM Bore; 90MM Outside Diameter; 13MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	6913LLU/2AS
Weight / LBS	0.458
Outside Diameter	3.543 Inch 90 Millimeter
Bore	2.559 Inch 65 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricated
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	65 mm
precision rating:	ISO Class 0



Shandong Jiangshan Industrial Develop...

outside diameter:	90 mm
finish/coating:	Uncoated
overall width:	13 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	13 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	13 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	4000 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	8200 RPM
dynamic load capacity:	17400 N
series:	69
static load capacity:	16100 N
manufacturer product page:	Click here