



7311 BEGBY Bearing 2D drawings and 3D CAD models

55 mm x 120 mm x 29 mm SKF 7311 BEGBY angular contact ball bearings

Bearing No. 7311 BEGBY

Size	120x55x29 mm
Bore Diameter	120 mm
Outer Diameter	55 mm
Width	29 mm
d	55 mm
D	120 mm
B	29 mm
d ₁	80.3 mm
d ₂	66.66 mm
D ₁	96.6 mm
a	51 mm
r _{1,2} - min.	2 mm
r _{3,4} - min.	1 mm
d _a - min.	66 mm
D _a - max.	109 mm
D _b - max.	114 mm
r _a - max.	2 mm
r _b - max.	1 mm
Basic dynamic load rating - C	85.2 kN
Basic static load rating - C ₀	60 kN
Fatigue load limit - P _u	2.6 kN
Reference speed	6700 r/min
Limiting speed	6700 r/min
Calculation factor - k _r	0.1

Calculation factor - k_a	1.6
Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - Y_0	0.52
Calculation factor - Y_1	0.55
Calculation factor - Y_2	0.93
Calculation factor - X	0.35
Calculation factor - Y_0	0.26
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.4
EAN	7316576650680
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Preload	Medium
Mounting Arrangement	Universal



Shandong Jiangshan Industrial Develop...

Inch - Metric	Metric
Long Description	55MM Bore; 120MM Outside Diameter; 29MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7311 BEGBY
Weight / LBS	3.078
Bore	2.165 Inch 55 Millimeter
Width	1.142 Inch 29 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter
bore diameter:	55 mm
radial static load capacity:	60 kN
outside diameter:	120 mm
cage material:	Brass
overall width:	29 mm
outer ring width:	29 mm
contact angle:	40 °
maximum rpm:	6700 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	2 mm

radial dynamic load capacity:	85.2 kN
series:	73
d_1	80.3 mm
d_2	66.66 mm
D_1	96.6 mm
$r_{1,2}$ min.	2 mm
$r_{3,4}$ min.	1 mm
d_a min.	66 mm
D_a max.	109 mm
D_b max.	114 mm
r_a max.	2 mm
r_b max.	1 mm
Basic dynamic load rating C	85.2 kN
Basic static load rating C_0	60 kN
Fatigue load limit P_u	2.55 kN
Calculation factor A	0.0627
Calculation factor k_r	0.1
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	1.4 kg